

# DENTO PAWĀ 4T

## 15W-40



### PRODUCT DESCRIPTION

DENTO PAWĀ 4T 15W-40 is a high quality mineral engine oil for modern four cycle engines of sport bikes, all terrain vehicles, motorcycles and other two-wheel motor applications with air or liquid cooling.

The product is manufactured using highly refined mineral base stocks, a premium additives package, and additional friction modifiers to provide smooth and noiseless clutch friction performance in general oil sump.

DENTO PAWĀ 4T 15W-40 possesses outstanding oxidation stability and increased high shear stability, which provide reliable and effective performance of engine parts under extreme loads. Highly effective detergents and dispersants maintain engine cleanliness and prevents the buildup of high temperature deposits on spark plugs in the combustion chamber and valves.

### APPLICATION

- DENTO PAWĀ 4T 15W-40 is engineered specially for high efficiency four-cycle engines of sport bikes, all-terrain vehicles and motorcycles, which require the use of JASO MA2 or JASO MA compliant engine oils. DENTO PAWĀ 4T 15W-40 is specially recommended for motorbikes operating in extremely hot climate regions.
- DENTO PAWĀ 4T 15W-40 is the best choice for high output four-cycle gasoline engines of cars operating under ultimate loads, when oil does not have sufficient time to cool.

### CUSTOMER BENEFITS

- The thoroughly balanced product formulation maintains initial performance characteristics of oil for extended service life and allows effective operation of motorbikes under extreme loads and increased operating temperature.
- DENTO PAWĀ 4T 15W-40 effectively protects loaded parts against wear due to the excellent oil film stability to shear. The product contributes to maximum durability of the engine.
- The application of selected highly refined base stocks and the unique low ash additive package guarantees outstanding compatibility of product with catalytic converters and the possibility of their long service life.

### MEETS SPECIFICATIONS AND REQUIREMENTS OF:

- API SL
- JASO MA / MA2

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

### TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	ASTM
SAE Grade		15W-40	
Kinematic viscosity at:			
40°C	cSt	107.2	ASTM 445
100°C	cSt	14.62	ASTM 445
Flash point	°C	238	ASTM D92
Pour point	°C	-36	ASTM D97
Density at 30°C	kg/l	0.865	ASTM D4052
Viscosity index		140	ASTM D2270
Color		L 3.0	ASTM D1500

### **STORAGE AND HANDLING GUIDELINES**

- Avoid exposing products to direct sunlight.
- Cans, packed in cardboard boxes, must be stored in dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors on pallets and racks.
- If stored outdoors drums should be placed sidewise to avoid accumulation of moisture.

### **HEALTH, SAFETY AND ENVIRONMENT PROTECTION**

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.