

DENTO Flush Out



PRODUCT DESCRIPTION

DENTO Flush Out is a flushing oil that is specifically engineered for purge of internal combustion engine lubrication systems without the need for tear down. The product is manufactured using highly refined base stocks with hydrocracking technology possessing high stability and high viscosity index. The product contains a specially selected additives package consisting of an effective combination of detergent, dispersant and anti-wear additives. During a short period (10-20 minutes of warm engine work) the oil gradually washes away accumulated deposits in oil passages and interior cavities of the engine. DENTO Flush Out effectively removes solid and semi solid wear particles from loaded engine components.

APPLICATION

- DENTO Flush Out is recommended for gasoline and diesel engines of passenger cars and off-road vehicles during oil change after operations with extended service interval.
- The product is recommended in cases when high level of contamination in lubrication system and sump has occurred.
- It is recommended to use the product when shifting to a higher service category of oil (ACEA or API) in order to remove deposits in hot areas of the engine.

- The product is recommended for repair works, such as engine head gasket change, after engine overheating, in circumstances where the customer has failed to observe proper drain intervals.
- Instruction: After draining the used engine oil, pour DENTO Flush Out into the reservoir, run engine at a fast idle for about 10- 20 minutes. Finally, drain flushing oil and refill with a suitable Totachi lubricant.

CUSTOMER BENEFITS

- Excellent detergent additive removes sludge and soot layer by layer. The product provides deposit dispersancy and prevents plugging of oil passages and filters.
- The product protects loaded components from wear during flush, thus maintaining maximum engine durability.
- DENTO Flush Out oil is fully compatible with different types of engine oils, recommended for modern four-stroke engines.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	ASTM
Kinematic viscosity at: 40°C 100°C	cSt cSt	33.1 5.8	ASTM 445 ASTM 445
Viscosity index		117	ASTM D2270
Density at 30°C	kg/l	0.846	ASTM D4052
Flash point	°C	230	ASTM D92
Pour point	°C	-42	ASTM D97
Color		L0.5	ASTM D1500

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Cans, packed in cardboard boxes, must be stored in dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors on pallets and racks.
- If stored outdoors drums should be placed sidewise to avoid accumulation of moisture.

HEALTH, SAFETY AND ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.