

DENTO PAWĀ 4T

10W-40



PRODUCT DESCRIPTION

DENTO PAWĀ 4T 10W-40 is premium engine oil for modern four cycle engines of sport bikes, all terrain vehicles, motorcycles and scooters, operating in intensive duty cycles under increased loads.

The product formulation is developed using highly refined mineral base stocks and unique additives package, and additionally friction modifiers to provide smooth and noiseless clutch friction performance in general oil sump.

DENTO PAWĀ 4T 10W-40 possesses outstanding oxidation stability and increased high shear stability, which provide reliable and effective performance of engine parts under ultimate loads and in high operating temperatures.

APPLICATION

- DENTO PAWĀ 4T 10W-40 is recommended for high output four cycle gasoline engines of motorcycles, all terrain vehicles and scooters, which require engine oils, meeting requirements of JASO MA2 or JASO MA.
- DENTO PAWĀ 4T 10W-40 is the best choice for high output four cycle gasoline engines of sport cars, operating under high loads, where the use of conventional oils is not optimal due to the loss of

oil's protection performance in high operating temperatures.

CUSTOMER BENEFITS

- DENTO PAWĀ 4T 10W-40 effectively protects highly loaded parts against wear due to the excellent oil film stability to shear and contributes to engine maximized performance.
- The use of a selected blend of highly refined base oils with high viscosity index provides outstanding low temperature flow rate and easy cold start of engine in low ambient temperatures without prior warm-up.
- The thoroughly balanced product formulation maintains initial performance characteristics of oil for extended service life and allows to maximize service intervals of motorcycles.

MEETS SPECIFICATIONS AND REQUIREMENTS OF:

- API SL;
- JASO MA / MA2 (T903.2011).

Before using this product make sure, it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	ASTM
SAE Grade		10W-40	
Kinematic viscosity at:			
40 °C	cSt	102,0	ASTM 445
100 °C	cSt	14,7	ASTM 445
Flash point	°C	236	ASTM D92
Pour point	°C	-36	ASTM D97
Density at 30°C	kg/l	0,863	ASTM D4052
Viscosity index		149	ASTM D2270
Color		L 2,5	ASTM D1500

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Cans, packed in cardboard boxes, must be stored in dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors on pallets and racks.
- If stored outdoors drums should be placed sidewise to avoid accumulation of moisture.

HEALTH, SAFETY AND ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.