

PRODUCT DESCRIPTION

TOTACHI® Air Intake & Carb Cleaner is a professional and highly efficient cleaner that quickly and effectively cleans carburetor channels and chambers, jets, throttle valves, and crankcase ventilation valve. Dissolves and removes all types of contaminants such as resin, carbon deposits and other deposits of waste substances formed during operation. Restores engine power, improves engine starting, normalizes fuel consumption and reduces exhaust toxicity. As a preventive measure, it can be used 2-3 times a year.

TOTACHI® Air Intake & Carb Cleaner is a specially developed formula for professional use that allows you to quickly achieve results. High efficiency, low product consumption, thanks to economical spray dispensers, will allow you to save on service station costs.

APPLICATION

Recommended for use in automotive repair shops. It is a professional product for cleaning the carburetor and intake system. Developed with strict adherence to the highest standards of quality and safety.

Shake the can before use. Start and warm up the engine, remove the air filter with its housing. With the engine running, spray the product in small portions into the carburetor cavity, on throttle valves and systems that require cleaning. At the same time, slightly open the throttle valve and increase the speed. Prevent the engine from stalling. After cleaning, adjust to idle speed, if it is required by the cleaning regulations. For ease of use, use the supplied extension tube.

WARRANTY

TOTACHI® Air Intake & Carb Cleaner meets or exceeds industry requirements. TOTACHI® guarantees full compliance with the written specifications indicated on product labels.

CUSTOMER BENEFITS

- **Clean engine**
Removes traces of waste oil deposits.
- **Improved engine performance**
Improves starting and restores engine power characteristics.
- **Environmentally friendly**
Reduces exhaust toxicity.
- **Optimized fuel consumption**
Normalizes fuel consumption.
- **Economical**
Low product consumption thanks to economical spray dispensers will allow you to save on service station costs.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES
Appearance	-	Clear liquid
Flash Point	°C	25
Boiling Point	°C	>75
Specific Gravity at 25°C	kg/L	1.0 – 1.2
Evaporation Rate	-	Slow

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

HEALTH, SAFETY & ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.