

PRODUCT DESCRIPTION

DENTO Coolant Red -30°C is a ready to use conventional coolant formulated to provide optimal protection against overheating, freezing and corrosion in cars, motorcycles, SUV, vans, and light duty trucks. It ensures smooth engine operation across a wide range of temperatures. It provides optimal performance and longevity of engine's cooling system. It enhances year-round protection against rust, corrosion, scale build up and cavitation of the cooling system.

DENTO Coolant Red -30°C is suitable for most gasoline & diesel engines. Regular use of this coolant helps maintain the engine's cooling efficiency, thus preventing unnecessary repairs caused by overheating. It is compatible with various cooling systems to reduce the need for keeping multiple types of coolants. Prevents common cavitation and increase the life of water pumps. Compatible with cast iron, aluminum, all ferrous alloys, rubber, seals, gaskets, and all components of the cooling system.

APPLICATION

Recommended for use in motorcycles, passenger cars, vans, SUVs, LCVs, light duty trucks, and agricultural machinery requiring coolants based on conventional technology.

Ready to use coolant with freeze point of -30°C. No need to add water. Safe to mix with genuine coolants based on conventional technology.

It is recommended to replace this coolant on a yearly basis to maintain optimum performance of the cooling systems.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	STANDARDS
Appearance	-	Transparent liquid without residue	Visual
Colour	-	Red	Visual
Density at 20 °C	g/cm ³	1.0638	ASTM D4052
pH	-	9.80	-

WARRANTY

DENTO Coolant Red -30°C meets or exceeds the OEM's warranty requirements of automotive and industrial applications where a ready to use coolant is required. TOTACHI® guarantees full compliance on the written specifications indicated on product labels.

CUSTOMER BENEFITS

- Reliable Protection**
 Prevents engine overheating and freezing to avoid engine breakdowns and costly repairs.
- Prolongs the Life of Cooling System**
 Protects against rust, corrosion, and pitting. Protects against surface cavitation. Enhanced water pump performance.
- Mixed Fleet Application**
 Suitable for use in automotive gasoline and light-duty diesel engines of multiple OEMs.
- Safe for Cooling System Components**
 Compatible with seals and hose materials to ensure protection of water pumps and prevent leakages.

MEETS SPECIFICATIONS & REQUIREMENTS OF:

- ASTM D3306

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

HEALTH, SAFETY & ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.

ATTENTION

DENTO Coolant Red -30°C is ***poisonous and extremely hazardous if ingested.***

When changing coolant, dispose used product in accordance with local, regional, or federal legislative provisions.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.