

### PRODUCT DESCRIPTION

TOTACHI® Multi-Use Product TG-40 is a universal grease with high penetrating properties for workshops and household use. It quickly lubricates the rusty parts, eliminates creaking, and provides easy disassembly of jammed parts. Suitable for use in lubricating gears, chains, lightly loaded bearings, locks, wheels, rollers, nuts, bolts, valves, seals, levers, handles, and door hinges. Penetrates micro cracks and narrow gaps. Displaces moisture from the metal surface and can be used as a lock defroster. Forms a stable film to protect against corrosion and oxidation processes.

### APPLICATION

Recommended for use in cleaning the surfaces and lubricating car parts, designed to meet all the quality and safety requirements. Returns functionality to locks and hinges. Provides easy assembly of corroded threaded connections. Recommended for use in car repair shops.

Suitable for use in lubricating other parts that slides, rolls, squeaks, and swivels. Can be used in bikes, power tools, hand tools, household applications, and workshops.

Shake the can before use. Spray the compound in a thin layer on the processed parts using the attached extension tube. Electrical devices can be connected to the power source in 10 minutes after applying the product.

### WARRANTY

TOTACHI® Multi-Use Product TG-40 meets or exceeds industry requirements. TOTACHI® guarantees full compliance with the written specifications indicated on product labels.

### CUSTOMER BENEFITS

- **Efficiency Easy assembly and disassembly of parts**  
A professional tool that provides easy disassembly and assembly of parts.
- **Protection against corrosion and oxidation**  
Forms a protective polymer layer on the treated surfaces, preventing corrosion and oxidation processes.
- **Cleanliness of vehicle parts**  
Cleans surfaces and lubricates parts without leaving greasy or sticky residue.
- **Moisture resistance**  
Lubricates, displaces, and preserves moisture, allowing deep penetration into hidden and hard-to-reach cavities.
- **Economical**  
Low product consumption thanks to economical spray dispensers will allow you to save on service station costs.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

### ***TYPICAL TEST DATA***

CHARACTERISTICS	UNITS	VALUES
Color	-	Brownish Transparent Liquid
Density	kg/L	0.79 – 0.82
Solubility	-	Non-soluble in water
Flash Point	°C	<0
Adhesion on metal	-	Excellent

### ***STORAGE AND HANDLING GUIDELINES***

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

### ***HEALTH, SAFETY & ENVIRONMENT PROTECTION***

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.