

## PRODUCT DESCRIPTION

TOTACHI® Octane Booster is a professional fuel additive formulated to increase the gasoline octane number and clean the fuel system. The product eliminates knocking and detonation caused by low octane fuel, cleans and provides wear protection in the fuel system, restores the power and acceleration of the vehicle. Significantly improves the throttle response and torque for smoother driving conditions.

TOTACHI® Octane Booster does not contain alcohol and is safe for use in vehicles with catalytic converters and oxygen sensors. It improves fuel's resistance to ignition under high pressure and temperature to help the engine maintain its performance even pushed to its limits.

## APPLICATION

Recommended for use as DIY octane booster or in automotive repair shops. It increases the octane number of gasoline and cleaning the fuel system. Developed with strict adherence to the highest standards of quality and safety.

Shake the can before use. Add one can of 300ml TOTACHI® Octane Booster to 60 liters of gasoline fuel, either before or after fueling the tank. Typically, 1 can treats a full tank.

Use regularly when filling up the tank. For ease of use, use the supplied nozzle when pouring the product into the fuel tank.

## WARRANTY

TOTACHI® Octane Booster meets or exceeds industry requirements. TOTACHI® guarantees full compliance with the written specifications indicated on product labels.

## CUSTOMER BENEFITS

- **Enhance Engine Performance**  
The increase of octane number significantly reduces the knocking and detonation in the engine,

allowing smoother combustion. Thus, increasing the horsepower & torque for improved acceleration and efficiency engine operation.

- **Durable Engine**  
Improves fuel combustion and reduces stress on internal engine parts, both can prevent excessive wear and tear to the engine.
- **Improved Fuel Efficiency**  
Engines run more efficiently which leads to reduced fuel consumption over time.
- **Clean engine**  
Removes traces of contaminants and deposits in the fuel system. This helps in the optimal combustion function which leads to increase in engine performance.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

**TYPICAL TEST DATA**

CHARACTERISTICS	UNITS	VALUES
Appearance	-	Clear liquid
Color	-	Colourless
Specific Gravity	kg/L	0.80
Boiling Point	°C	>60
Flash Point	°C	<20

**STORAGE AND HANDLING GUIDELINES**

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

**HEALTH, SAFETY & ENVIRONMENT PROTECTION**

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.