**COTACHI**<sup>®</sup> ULTIMA RACING MOTO 4T 10W-40 UHP Fully Synthetic

#### **PRODUCT DESCRIPTION**

TOTACHI ULTIMA RACING MOTO 4T 10W-40 is a 100% synthetic 4-stroke motorcycle racing engine oil, specifically engineered for motorsport applications and high-performance riding conditions. Formulated with premium PAO and Esters base oils, enhanced with advanced chemical components to maximize engine power output while delivering superior protection of the clutch, gearbox and all engine components. Outstanding performance over long distances, especially in endurance or track races. Prevents premature engine wear and ensures engine reliability during demanding races.



Developed exclusively with TOTACHI's core motorcycle racing technology, **INFINITE+™**, featuring an advanced additive componentry and a superior blend of high-quality PAO & Esters. This combination guarantees exceptional durability, cleanliness and protection,

while delivering continuous power and performance throughout the race.



Unique frictional properties to effectively balance power efficiency and fuel economy, while ensuring optimal clutch friction engagement and

durability. It enhances power output, enables smoother gear shifting and maintains a cooler engine, delivering reliable performance even in demanding riding conditions.

TOTACHI ULTIMA RACING MOTO 4T 10W-40 minimizes wear and maintains its protective properties even under sustained high temperatures. Excellent detergency and oxidation properties to prevent sludge build-up and keep engine at its peak during oil service life. Enhanced to ensure excellent strength of oil film under high temperature high shear conditions to minimize metal-to-metal contact, reducing wear and ensuring the overall health of the engine.

The exceptional performance of TOTACHI ULTIMA RACING MOTO 4T range makes it a perfect choice for racing enthusiasts.

## APPLICATION

For use in all 4-stroke motorcycles in racetracks or road bikes. Formulated for racing bikes, sport bikes, motocross bikes, supercross bikes, enduro bikes, dirt track bikes, street bikes, trail bikes, and other bikes for on-road & off-road races where a SAE 10W-40 grade is recommended. Also suitable for use in ATVs and UTVs.

#### WARRANTY

TOTACHI ULTIMA RACING MOTO 4T 10W-40 meets or exceeds the OEM's warranty requirements of 4-stroke requiring API SP or lower engine oil. TOTACHI<sup>®</sup> guarantees full compliance on the written specifications indicated on product labels.

#### **CUSTOMER BENEFITS**

#### • Ultimate performance

TOTACHI ULTIMA RACING MOTO 4T range is formulated using unique TOTACHI **ZFM+**<sup>™</sup> technology for maximum oil film strength and outstanding wear protection of all engine parts during extreme driving conditions.

#### • Engine durability

Robust technology perfectly formulated for maximum protection of engines, clutch and gearbox over the oil service life.

#### • Outstanding cleanliness and deposit control

Advanced detergent and dispersant components that keep engine clean generated during extreme riding conditions, thus improving the overall engine performance and extending engine life.

#### • Excellent compatibility

Product is fully compatible with all engine components, meets the latest environmental standards for modern engines.

#### **MEETS SPECIFICATIONS AND REQUIREMENTS OF:**

- Race performance
- API SP
- JASO MA2

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TOTACHI INDUSTRIAL CO., LTD. Japan, web: www.totachi.com

<sup>©</sup>All rights reserved. TOTACHI, TOTACHI, NIRO<sup>™</sup>, NIRO. "Get confidence in motion ™" and ZFM™ antifriction technology are the property of TOTACHI NDUSTRIAL CO. LTD. All other trademarks are the property of their respective owners..

# TOTACHI® , ULTIMA RACING MOTO 4T 10W-40 **UHP Fully Synthetic**

### TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	STANDARDS
SAE Grade	-	10W-40	SAE J300
Kinematic viscosity at:			
40 °C	cSt	87.64	ASTM D445
100 °C	cSt	13.92	ASTM D445
Viscosity index	-	163	ASTM D2270
Cranking viscosity at -25°C	mPa-s	4362	ASTM D5293
Color	-	L2.5	ASTM D1500
Flash point	°C	248	ASTM D92
Pour point	°C	-33	ASTM D97
Density at 30 °C	kg/L	0.8457	ASTM D4052
Total Base Number	mg KOH/g	6.9	ASTM D2896

# STORAGE AND HANDLING GUIDELINES

- Store in cool and dry places. Avoid exposing products to . moisture.
- Avoid exposing products to direct sunlight.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

## HEALTH, SAFETY AND ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO., LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI<sup>®</sup> distributor.

TOTACHI INDUSTRIAL CO., LTD. Japan, web: <u>www.totachi.com</u> ©All rights reserved. TOTACHI, NTACHI,NIRO™, NIRO. "Get confidence in motion ™" and ZFM™ antifriction technology are the property of TOTACHI NDUSTRIAL CO. LTD. All other trademarks are the property of their respective owners..