

### PRODUCT DESCRIPTION

Hyper Ecodrive 5W-30 is an innovative fuel efficiency fully synthetic, Resource Conserving, engine oil formulated for use in next-generation gasoline engines – turbocharged gasoline direct injections (TGDI), hybrid electric vehicles (HEV), plug-in hybrid electric vehicles (PHEV), range extended electric vehicles (REEV), battery-assisted hybrid vehicles (BAHV), Extended Range Electric Vehicle (EREV) and all other vehicles operating under severe urban conditions where “Stop-Start” modes are typical. Exceptional wear protection, withstands high temperature oxidation, excellent cleaning power and ideal for use in high power density engines requiring a robust oil. Outstanding friction properties to optimize the fuel economy benefit from a 5W-30 engine oil. Guaranteed protection against Low Speed Pre-Ignition (LSPI) and timing chain wear.



Hyper Ecodrive 5W-30 is enhanced with unique anti-friction technology, ZFM™ (Zero Friction Molecular), to considerably reduce friction and wear of highly loaded engine parts that are exposed to intensive duty cycles and high operating temperatures.

Effectively prevents deposits and sludge build up to prolong the engine life.

### APPLICATION

Recommended for all types of gasoline fueled engines requiring a viscosity grade of SAE 5W-30 API SP, ILSAC GF-6A, Resource Conserving engine oil. For passenger cars, vans, CUVs, SUVs, light duty trucks and other vehicles fitted with recent gasoline engines. Helps protect engines operating on E85 fuels.

Backward compatible to API SN PLUS, API SN, ILSAC GF-5.

### WARRANTY

Hyper Ecodrive 5W-30 meets or exceeds the OEM's warranty requirements of gasoline vehicles where API SP and ILSAC GF-6A oil is required. TOTACHI® guarantees full compliance on the written specifications indicated on product labels.

### CUSTOMER BENEFITS

- **Fuel Efficient**  
Good friction properties, easy start up in cold weather, better oil pumpability and excellent low temperature properties to support effective lubrication and fuel savings even in severe driving conditions.
- **Superior Engine Durability**  
Robust engine oil designed for downsized engines with higher horsepower and torque. With carefully selected components to ensure protection against premature combustion, known as LSPI which can cause catastrophic engine failure. Additional timing chain wear protection for a maximized engine durability.
- **Optimized Drain Intervals**  
Outstanding high temperature stability for superior control of sludge, varnish, rust, corrosion and other harmful deposits to ensure maximum engine oil life.
- **Hybrid Vehicles**  
Provides optimum lubrication and wear protection on engines running less during low speed and stop-and-go driving.
- **Compatibility with ECS (Emission Control System)**  
The low content of phosphorus and ash contributes to the long life of the three-component catalytic converters (TWC).

### MEETS SPECIFICATIONS & REQUIREMENTS OF:

- API SP
- ILSAC GF-6A
- Resource Conserving
- FORD WSS-M2C946-B1 / 946-A
- CHRYSLER MS-6395
- FIAT 9.55535-CR1
- GM Dexos 1



Suitable for use in various OEMs such as TOYOTA, GENESIS, HONDA, HYUNDAI, KIA, INFINITI, MITSUBISHI, LEXUS, GEELY, NISSAN, MG, SUZUKI, CHEVROLET, DATSUN, SUBARU, FORD, HOLDEN, MAZDA, CHRYSLER, ACURA, DODGE, FIAT and other OEMs requiring a SAE 5W-30, API SP, Resource Conserving and ILSAC GF-6A.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

### TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	STANDARDS
SAE Grade	-	5W-30	SAE J300
Kinematic viscosity at:			
40 °C	cSt	56.16	ASTM D445
100 °C	cSt	9.79	ASTM D445
Viscosity index	-	161	ASTM D2270
Cranking viscosity at -30°C	mPa-s	4889	ASTM D5293
Color	-	L2.0	ASTM D1500
Flash point	°C	224	ASTM D92
Pour point	°C	-42	ASTM D6892
Density at 30 °C	kg/L	0.8392	ASTM D4052
Total Base Number	mg KOH/g	7.10	ASTM D2896

### STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

### HEALTH, SAFETY & ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI<sup>®</sup> distributor.