

COMPLETE FUEL SYSTEM CLEAN MOTO

PRODUCT DESCRIPTION

TOTACHI® Complete Fuel System Clean MOTO is a super concentrated fuel system cleaner that is added to 4-stroke or 2-stroke gasoline engines of motorcycles, scooters, sport bikes, street bikes, cruisers, mopeds, quads, all-terrain vehicles (ATV), 3-wheeler bikes, buggies, snowmobiles, and other road & off-road bikes. It thoroughly eliminates the deposits, dirt, sludge and varnish in the injectors, intake valves and combustion chamber which increase the compression and enhance the acceleration of engine to higher top speed. Excellent deep cleaning properties to restore the engine power and guarantee a smoother drive.

TOTACHI® Complete Fuel System Clean MOTO keeps the fuel system clean which contributes to the improvement in the fuel efficiency and effectively reduces emissions. The powerful cleaning properties of this product prolongs the engine life.

APPLICATION

Recommended for all types of 4-stroke and 2-stroke motorcycles. Suitable for use in gasoline engines running in all types of fuels. Boosts the overall performance of the engines by restoring the cleanliness of intake valves, fuel injectors and combustion chambers. Provides excellent lubrication during the deep cleaning phase while burning off the removed deposits.

Add one can of 60 ml TOTACHI® Complete Fuel System Clean MOTO to 20 liters of gasoline fuel. Recommended to use for 2 successive treatments. Then to be used every 5,000 km for deep cleaning action.

WARRANTY

TOTACHI® Complete Fuel System Clean MOTO meets or exceeds the OEM's warranty requirements of gasoline vehicles. Safe to add in 2-stroke engines where 2T oil and fuel are mixed. TOTACHI® guarantees full compliance on the written specifications indicated on product labels.

CUSTOMER BENEFITS

Powerful Drive

Deeply cleans the intake valve, fuel injector and combustion chamber for an optimum engine performance – powerful and accelerated drive.

Maximizes Fuel Economy

Guarantees good atomization of injectors to facilitate proper fuel distributor and effective air & fuel mixture during the combustion process.

• Reduces Harmful Emissions

Removes stubborn sludge and varnish from the intake valves and combustion chambers which significantly help in lowering the CO and emissions.



Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	STANDARDS
Kinematic viscosity at:			
40 °C	cSt	4.82	ASTM D445
Color	-	L0.5	ASTM D1500
Flash point	°C	86	ASTM D92
Pour point	°C	-45	ASTM D6892
Density at 30 °C	kg/L	0.8344	ASTM D4052



COMPLETE FUEL SYSTEM CLEAN MOTO

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

HEALTH, SAFETY & ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.