

PRODUCT DESCRIPTION

Premium NRO 68 is a HLP performance hydraulic oil for on-road and off-road applications and industrial equipment running in higher pressure and temperatures. Formulated with superior quality zinc containing additives to ensure effective wear protection to ensure maximum equipment life. Excellent resistance to oxidation minimizes the sludge and deposit formations, keeping the hydraulic system clean and efficient. Reduces machine downtime and enable cost savings. Good filterability characteristics and water separation for increased equipment reliability. Fast air release to prevent excessive foam formation for efficient hydraulic power transfer.

Premium NRO 68 meets the requirements of today's hydraulic equipment where filterability, wear protection, oxidation stability, air release, foam inhibition, demulsibility, hydrolytic stability, thermal stability, rust and corrosion protections are strictly demanded.

APPLICATION

Recommended for use in modern high pressure hydraulic systems, which require anti-wear zinc containing additives for effective protection against deterioration. For hydraulic systems in which axial piston, gear, vane, and other pumps are used.

WARRANTY

Premium NRO 68 meets or exceeds the OEM's warranty requirements of hydraulic systems where zinc containing additives of hydraulic oil with an ISO viscosity grade 68 is needed. TOTACHI® guarantees full compliance on the written specifications indicated on product labels.

TYPICAL TEST DATA

CHARACTERISTICS	UNITS	VALUES	STANDARDS
ISO Grade	-	68	
Kinematic viscosity at:			
40 °C	cSt	67.55	ASTM D445
100 °C	cSt	8.70	ASTM D445
Viscosity index	-	100	ASTM D2270
Color	-	L0.5	ASTM D1500
Flash point	°C	236	ASTM D92
Pour point	°C	-18	ASTM D6892
Density at 30 °C	kg/L	0.8756	ASTM D4052

CUSTOMER BENEFITS

- Equipment Durability**
 Reliable anti-wear protection even in severe operating conditions. Excellent filterability and pump wear performance.
- Excellent Water Demulsibility**
 Rapid water separation properties to help in the reduction of sludge and deposits, leading to an increased efficient and system reliability.
- Saves Cost**
 Maximizes oil drain intervals and ensures durability of hydraulic systems to cut operating downtime and untimely maintenance.

MEETS SPECIFICATIONS & REQUIREMENTS OF:

- AFNOR NF E 48-603 HM
- AFNOR NF E 48-690
- AFNOR NF E 48-691
- BOSCH REXROTH RDE-90220 (HLP)
- CINCINNATI MACHINE P-69
- DENISON HF-0, HF-1, HF-2
- DENISON T6C-020 VANE PUMP
- DIN 51 524 Part 1 (HL)
- DIN 51 524 Part 2 (HLP)
- EATON BROCHURE 694, 03-401-REV 2010
- EATON VICKERS I-286-S
- ZF TE ML 07M
- ZF TE ML 21M
- ISO 11158

Suitable for use in hydraulic systems requiring zinc containing additives.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

HEALTH, SAFETY & ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings, or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.