

PRODUCT DESCRIPTION

Dento Moto 4T 20W-50 is a premium motorcycle engine oil designed for 4-stroke engines. Highly recommended for use in street bikes, off-road bikes, mopeds, underbones, ATVs, buggies and other air-cooled or liquid-cooled 4-stroke motorcycle engines.

Dento Moto 4T 20W-50 provides excellent lubricating properties on the most critical areas of a motorcycle - engine, gearbox & clutch. Effectively minimizes wear and extends the engine life. Ensures a perfect clutch lock up during start-up, revving and full speed ride.

APPLICATION

Recommended for all types of 4-stroke gasoline motorcycle engines requiring a viscosity grade of SAE 20W-50 and JASO MA oils. Suitable for older engines requiring thicker oils. Ideal for bikes working under severe operating temperatures. Applicable for use in warmer climates.

WARRANTY

Dento Moto 4T 20W-50 meets or exceeds the OEM's warranty requirements of 4-stroke motorcycles where API SG and JASO MA oil is required. TOTACHI® guarantees full compliance on the written specifications indicated on product labels.

TYPICAL TEST DATA

| CHARACTERISTICS | UNITS | VALUES | STANDARDS |
|-------------------------|----------|--------|------------|
| SAE Grade | - | 20W-50 | SAE J300 |
| Kinematic viscosity at: | | | |
| 40 °C | cSt | 193.40 | ASTM D445 |
| 100 °C | cSt | 20.82 | ASTM D445 |
| Viscosity index | - | 127 | ASTM D2270 |
| Color | - | 2.0 | ASTM D1500 |
| Flash point | °C | 258 | ASTM D92 |
| Pour point | °C | -30 | ASTM D97 |
| Density at 30 °C | kg/L | 0.9669 | ASTM D4052 |
| Total Base Number | mg KOH/g | 5.7 | ASTM D2896 |

CUSTOMER BENEFITS

- Engine durability**
 Powerful cleaning agents for better control on sludge formation. Plus, active anti-wear components to minimize engine and gear wear.
- Smooth riding experience**
 Easy gear shifts, perfect clutch lock up during start up, high revving and full speed ride.
- Lesser oil top ups**
 Formulated to provide lesser oil loss even at high operating conditions.

MEETS SPECIFICATIONS AND REQUIREMENTS OF:

- API SG
- JASO MA

Suitable for use in various OEMs requiring a 20W-50, API SG & JASOM MA oils.

Before using this product, ensure it is consistent with OEM's recommendations for the equipment operating conditions and customer's maintenance practices.

STORAGE AND HANDLING GUIDELINES

- Avoid exposing products to direct sunlight.
- Store in cool and dry places. Avoid exposing products to moisture.
- It is highly recommended to store drums indoors or under cover on pallets and racks.

HEALTH, SAFETY AND ENVIRONMENT PROTECTION

Information on health, safety and environment protection is described in the product Safety Data Sheet (SDS). The SDS file contains details on potential hazards, precautions and first aid measures, as well as information on environmental impact and disposal of used products.

TOTACHI INDUSTRIAL CO. LTD. disclaims any liability in case the product is used with violation of these instructions and warnings or it is not used for its intended purpose. Before using product other than intended, consult your local TOTACHI® distributor.